**TRG d.o.o.**
**Celovška cesta 150, 1000 Ljubljana**

**Davčna št.:** SI 56119488
**Telefon:** 01 500 14 42
**E-mail:** info@podjetje-trg.si
**WWW:** www.www.karcher-trg.si

**Datum:** 23.11.2026

# T-kos 130, N.N./N.N./N.N.Rp 2 1/2T-kos Rp 1 1/4




(slika je simbolična)

Kategorija: Tee 130, reducing, female/female/female
Šifra: **112993RIE**

## Kratek opis

T-piece 130, IT/IT/IT, Rp 2 1/2, T-branch redu. Rp 1 1/4, Operating temp. -20°C to 300°C, black malleable cast iron, Hot-dip galv.
"
Acc. to DIN EN 10242 (formerly DIN 2950)
The classic - and the most popular - screw fitting series for pipe construction.
These fittings are characterized by their high mechanical strength and surface quality to DIN 2444.
They are completely coated with a layer of pure zinc and are therefore suitable for drinking water

## Tehnične Specifikacije

| | |
|---|---|
| Min. temperaturno območje [°C] | -20 |
| Material | Black malleable iron B350-10, design symbol A |
| Navoj 1 | Rp 2 1/2 |
| Navoj 2 Zmanjšana razvejanost | Rp 1 1/4 |
| Navoj 3 | Rp 2 1/2 |
| Površina | Hot dip galvanised |
| Standardni navoj | acc. ISO 7-1 |
| Max. temperaturno območje [°C] | 300 |