TRG d.o.o.
Celovška cesta 150, 1000 Ljubljana

Davčna št.: SI 56119488
Telefon: 01 500 14 42
E-mail: info@podjetje-trg.si
WWW: www.www.karcher-trg.si

Datum: 23.11.2026

T-kos 130, N.N./N.N./N.N.Rp 3/8T-kos Rp 1/4



(slika je simbolična)

Kategorija: Tee 130, reducing, female/female/female
Šifra: **112969RIE**

Kratek opis

T-piece 130, IT/IT/IT, Rp 3/8, T-branch reducing Rp 1/4, Operating temp. -20°C to 300°C, black malleable cast iron, Hot-dip galva.
"
Acc. to DIN EN 10242 (formerly DIN 2950)
The classic - and the most popular - screw fitting series for pipe construction.
These fittings are characterized by their high mechanical strength and surface quality to DIN 2444.
They are completely coated with a layer of pure zinc and are therefore suitable for drinking water

Tehnične Specifikacije

Min. temperaturno območje [°C]	-20
Material	Black malleable iron B350-10, design symbol A
Navoj 1	Rp 3/8
Navoj 2 Zmanjšana razvejanost	Rp 1/4
Navoj 3	Rp 3/8
Površina	Hot dip galvanised
Standardni navoj	acc. ISO 7-1
Max. temperaturno območje [°C]	300