

Datum: 26.06.2026

Davčna št.: SI 56119488
Telefon: 01 500 14 42
E-mail: info@podjetje-trg.si
WWW: www.karcher-trg.si



(slika je simbolična)

Temperaturna sklopka DN 9navoj 13 mmzaporni ventil,Fi 90°

Kategorija: [Temp. control coupling DN 9, with shut-off valve](#)
Šifra: **107955RIE**

Kratek opis

Tempered coupling DN 9, Taps 13 mm, Blocking valve, Brass, Hose sleeve 90°, Operating pressure max. 15 bar, Temp. -20 °C to 160 °C
Compatible with HASCO Z 8 system.
For temperature control applications involving hot or cold water or heat transfer oil.
Optionally with free passage, one or both sides sealing.
Female-threaded couplings and plugs with female-threaded PTFE seal.

Tehnične Specifikacije

Min. sobna temperatura [°C]	-20
Min. temperatura medija [°C]	-20
Krogla	Stainless steel
Material	Brass 2.0401
Pritrdilni obroč	Stainless steel
Srednje	Air, water, oil, vacuum
Tesnilo	FPM (PTFE coated)
Vzmet	Stainless steel
Priključek za cev [mm]	13
Max. obratovalni tlak [bar]	15
Dolžina [mm]	50.5
Tip stebelnih cevi	90°
Max. sobna temperatura [°C]	160
Max. temperatura medija [°C]	160