

Datum: 25.04.2026

Davčna št.: SI 56119488  
Telefon: 01 500 14 42  
E-mail: [info@podjetje-trg.si](mailto:info@podjetje-trg.si)  
WWW: [www.karcher-trg.si](http://www.karcher-trg.si)



(slika je simbolična)

## Temperdeča coupl. DN 9, navoj 13 mm, zaporni ventil, Fi cevi ravno

Kategorija: [Temp. control coupling DN 9, with shut-off valve](#)  
Šifra: **107953RIE**

### Kratek opis

Tempered coupling DN 9, Taps 13 mm, Blocking valve, Brass, Hose sleeve straight, Operating pressure max. 15 bar  
Compatible with HASCO Z 8 system.  
For temperature control applications involving hot or cold water or heat transfer oil.  
Optionally with free passage, one or both sides sealing.  
Female-threaded couplings and plugs with female-threaded PTFE seal.

### Tehnične Specifikacije

Min. sobna temperatura [°C]	-20
Min. temperatura medija [°C]	-20
Krogla	Stainless steel
Material	Brass 2.0401
Pritrdilni obroč	Stainless steel
Srednje	Air, water, oil, vacuum
Tesnilo	FPM (PTFE coated)
Tip stebelnih cevi	straight
Vzmet	Stainless steel
Priključek za cev [mm]	13
Max. obratovalni tlak [bar]	15
Dolžina [mm]	61.5
Max. sobna temperatura [°C]	160
Max. temperatura medija [°C]	160