

Datum: 27.05.2026

Davčna št.: SI 56119488
Telefon: 01 500 14 42
E-mail: info@podjetje-trg.si
WWW: www.karcher-trg.si



(slika je simbolična)

Tesnilno - zaporni ventil, nerjavno jeklo 1.4401/1.4408, G 3/8

Kategorija: [Female thread globe valves stainless steel](#)
Šifra: **103795RIE**

Kratek opis

Bushing - blocking valve, Stainless steel 1.4401/1.4408,
Medium / ambient temperature max. 160 °C, G 3/8, DN 10,
PN max. 14 bar

Tehnične Specifikacije

| | |
|-------------------------------|------------------------------------|
| Min. delovna temperatura [°C] | -10 |
| Kolo | Aluminium |
| Navoj | G 3/8 |
| Notranji deli | Stainless steel 1.4401 / 1.4408 |
| Ohišje | Stainless steel 1.4401 / 1.4408 |
| Tesnilo | PTFE |
| DN | 10 |
| Max. obratovalni tlak [bar] | 14 |
| L [mm] | 52.0 |
| A [mm] | 70.0 |
| B min. [mm] | 89.0 |
| B max. [mm] | 99.0 |
| Max. sobna temperatura [°C] | 160 |
| Max. temperatura medija [°C] | 160 |
| Max. delovna temperatura [°C] | 180 |