



(slika je simbolična)

## Throttle check valve, supply air, G 3/8, plug-in connector 8

Kategorija: [Unidirectional flow control valves, supply air V](#)  
Šifra: **113033RIE**

### Kratek opis

Throttle check valve, supply air (V), slotted-head screwdriver, G3/8, plug-in8, rotating, 0 to 10 bar, -20°C to 80°C, nickel-plated brass  
For throttling flow rates and regulating the piston speed of cylinders. Small dimensions, ideal for tight spaces. To be screwed directly into the valve or cylinder. The set flow rate can be locked via the lock nut in the version with knurled screw. The variants in banjo bolt construction can be rotated during assembly and are fixed after tightening. The variants with plug-in connector, rotated can also be rotated freely after assembly. The seals and lubricants used are silicone-free.

### Tehnične Specifikacije

|                                |                         |
|--------------------------------|-------------------------|
| Min. temperaturno območje [°C] | -20                     |
| Design                         | rotating                |
| Ffunkcija                      | Supply air throttle (V) |
| Navoj                          | G 3/8                   |
| Silicone-free                  | Yes                     |
| Telo                           | Nickel-plated brass     |
| Tesnilo                        | NBR                     |
| Vrsta povezave                 | Plug-in connector       |
| Za cevi [mm]                   | 8                       |
| Max. obratovalni tlak [bar]    | 10                      |
| a/f [mm]                       | 14                      |
| C [mm]                         | 26.5                    |
| B [mm]                         | 50.0                    |
| Max. temperaturno območje [°C] | 80                      |