



## Tlačni pretvornik, 0 - 400 bar, G 1/2, CrNi jeklo1.4571

Kategorija: [Wika](#)  
Šifra: **102707RIE**

(slika je simbolična)

### Kratek opis

Pressure transducer for general industrial applications, Non-linearity 0.2%, Measurement range 0-400 bar, G 1/2, CrNi steel 1.4571

Standard type for universal applications. Suitable for electronic pressure measurements in the low and high-pressure ranges.

### Tehnične Specifikacije

|                              |                                                        |
|------------------------------|--------------------------------------------------------|
| Min. temperatura medija [°C] | -30                                                    |
| Min. sobna temperatura [°C]  | -20                                                    |
| Deli v kontaktu z medijem    | CrNi steel 1.4571                                      |
| Električni priključek        | With right-angle connector acc. to DIN EN 175301-803 A |
| IP zaščita                   | IP 65 acc. to EN 60529                                 |
| Navoj                        | G 1/2                                                  |
| Ohišje                       | CrNi steel 1.4571                                      |
| Operativna napetost          | DC 10 ... 30 V                                         |
| Spodnja/Zgornja meja območja | Positive pressure                                      |
| Vrsta                        | S-10                                                   |
| Nelinearnost                 | 0.2% of span                                           |
| izhodni signal               | 4 - 20 mA, 2-wire                                      |
| Max. sobna temperatura [°C]  | 80                                                     |
| Max. temperatura medija [°C] | 100                                                    |
| Merilno območje max. bar     | 400                                                    |