



(slika je simbolična)

## Tlačni reg. s pnevmatskim dalj. upravljanjem »Stinard«G 1/2

Kategorija: [Pressure regulators pneumatic remote control](#)  
Šifra: **101252RIE**

### Kratek opis

Pressure regulator pneumatic remote controlled  
»Standard«, without pressure gauge, G 1/2, Input pressure  
max. 25 bar, max. 80 °C

Diaphragm pressure regulators, self-relieving, with  
pneumatic remote control.

The full functionality is assured in combination with a pilot  
regulator.

We recommend using one of our precision or standard  
pressure regulators with a G 1/4 port as the pilot regulator.  
The output pressure corresponds to the set pressure of the  
pilot pressure regulator.

To design a closed control loop similar to the sketch below  
please use our precision pilot regulator (feedback).

### Tehnične Specifikacije

Merjenje pretoka	At $P_1 = 8$ bar, $P_2 = 6$ bar and pressure drop $\Delta p = 1$ bar
Navoj	G 1/2
Navoj za pnevmatsko daljinsko upravljanje	G 1/4
Ohišje	Die-cast zinc
Serijska	Standard
Tesnilo	NBR
Max. vhodni tlak [bar]	25
B [mm]	74.0
Max. delovna temperatura [°C]	80
Max. temperatura medija [°C]	80
A [mm]	82.0
Pretok [l/min]	5800