



(slika je simbolična)

## Tlačni reg. s pnevmatskim dalj. upravljanjem »Stinard«G 1

Kategorija: [Pressure regulators pneumatic remote control](#)  
Šifra: **101254RIE**

### Kratek opis

Pressure regulator pneumatic remote controlled »Standard«, without pressure gauge, G 1, Input pressure max. 40 bar, max. 80 °C  
Diaphragm pressure regulators, self-relieving, with pneumatic remote control.  
The full functionality is assured in combination with a pilot regulator.  
We recommend using one of our precision or standard pressure regulators with a G 1/4 port as the pilot regulator. The output pressure corresponds to the set pressure of the pilot pressure regulator.  
To design a closed control loop similar to the sketch below please use our precision pilot regulator (feedback).

### Tehnične Specifikacije

Merjenje pretoka	At $P_1 = 8$ bar, $P_2 = 6$ bar and pressure drop $\Delta_p = 1$ bar
Navoj	G 1
Navoj za pnevmatsko daljinsko upravljanje	G 1/4
Ohišje	Aluminium
Serijska	Standard
Tesnilo	NBR
Max. vhodni tlak [bar]	40
Max. delovna temperatura [°C]	80
Max. temperatura medija [°C]	80
B [mm]	109.0
A [mm]	125.0
Pretok [l/min]	15000