



(slika je simbolična)

Tlačni regulator DRV 250, Low pressure design, G 3/8, 0.2-2 bar

Kategorija: [DRV 250 pressure regulator, low-pressure type](#)
Šifra: **101435RIE**

Kratek opis

Pressure regulator DRV 250, Low pressure design, non-reversible, incl. pressure gauge, G 3/8, Control range 0.2 - 2 bar

Diaphragm pressure regulators with non-self-relieving design and non-pressure-reduced single-seated valve. Very precise adjustment and good response characteristic because there are only a few moving parts and hence minimal friction.

Ideal for compressed air, nitrogen and other neutral, non-flammable gases, but only suitable for liquids with comparatively low flow rates.

Tehnične Specifikacije

Navoj	G 3/8
Ohišje	Red brass
	2.1096.01
Tesnilo	NBR
Vzmet pokrova motorja	Pressed brass
Min. krmilno območje [bar]	0.2
Pretok KVS vrednost [m ³ /h]	0.6
Max. krmilno območje [bar]	2
DN	10
Razmerje zmanjšanja max.	20:1
Max. vhodni tlak [bar]	25
D [mm]	45.5
A [mm]	70.0
Max. temperaturno območje [°C]	75
C [mm]	140.0
B [mm]	185.5