



(slika je simbolična)

## Tlačni regulator iz nerjevečega jekla, 1.4404, G 1/4, 0.5 - 8 bar

Kategorija: [Reversible, stainless steel pressure regulator](#)  
Šifra: **101191RIE**

### Kratek opis

Stainless steel pressure regulator, 1.4404, with secondary venting (reversible), G 1/4, Control range 0.5 - 8 bar  
Stainless steel regulators containing no non-ferrous metals for use in the food processing, chemical, mining, plant construction and special machinery industries as well as in the medical technology.

### Tehnične Specifikacije

Membrane	PTFE on NBR carrier At $P_1 = 8$ bar, $P_2 = 6$ bar and pressure drop $\Delta_p \leq 1$ bar
Merjenje pretoka	bar and pressure drop $\Delta_p \leq 1$ bar
Navoj	G 1/4
Ohišje	Stainless steel 1.4404 (AISI 316L)
Tesnilo	FKM
Min. krmilno območje [bar]	0.5
Max. krmilno območje [bar]	8
Max. vhodni tlak [bar]	30
C [mm]	37.0
A [mm]	64.0
Max. sobna temperatura [°C]	80
Max. temperatura medija [°C]	80
D [mm]	122.0
B [mm]	160.0
Pretok [l/min]	1300