

Datum: 08.04.2026



(slika je simbolična)

Tlačni regulator »Stinard-mali«, G 1/4, 0.5 - 16 bar

Kategorija: [Pressure regulators, independent of inlet pressure](#)Šifra: **100779RIE**

Kratek opis

Pressure regulator »Standard-mini«, incl. pressure gauge and control panel nut, G 1/4, Input pressure max. 25 bar, 0.5 - 16 bar

Compact, reversible diaphragm pressure regulators, independent of inlet pressure, with self-relieving design. The pressure setting can be locked by pushing the knob down.

Tehnične Specifikacije

Merjenje pretoka	At $P_1 = 8$ bar, $P_2 = 6$ bar and pressure drop $\Delta_p = 1$ bar
Navoj	G 1/4
Ohišje	Die-cast zinc, painted silver
Serijska	Standard-mini
Tesnilo	NBR
Vzmet pokrova motorja	POM-brass
Min. krmilno območje [bar]	0.5
DN	5
C [mm]	15.0
Max. krmilno območje [bar]	16
Max. vhodni tlak [bar]	25
Zaslona manometra max. [bar]	25
A [mm]	40.0
Max. sobna temperatura [°C]	60
Max. temperatura medija [°C]	60
D [mm]	61.3
B [mm]	76.3
Pretok [l/min]	330