

Datum: 08.06.2026



(slika je simbolična)

Tlačni regulator »Stinard-mali«, G 1/8, 0.5 - 10 bar

Kategorija: [Pressure regulators, independent of inlet pressure](#)Šifra: **100774RIE**

Kratek opis

Pressure regulator »Standard-mini«, incl. pressure gauge and control panel nut, G 1/8, Input pressure max. 25 bar, 0.5 - 10 bar

Compact, reversible diaphragm pressure regulators, independent of inlet pressure, with self-relieving design. The pressure setting can be locked by pushing the knob down.

Tehnične Specifikacije

| | |
|------------------------------|--|
| Merjenje pretoka | At $P_1 = 8$ bar, $P_2 = 6$ bar and pressure drop $\Delta_p = 1$ bar |
| Navoj | G 1/8 |
| Ohišje | Die-cast zinc, painted silver |
| Serijska | Standard-mini |
| Tesnilo | NBR |
| Vzmet pokrova motorja | POM-brass |
| Min. krmilno območje [bar] | 0.5 |
| DN | 5 |
| Max. krmilno območje [bar] | 10 |
| C [mm] | 15.0 |
| Zaslona manometra max. [bar] | 16 |
| Max. vhodni tlak [bar] | 25 |
| A [mm] | 40.0 |
| Max. sobna temperatura [°C] | 60 |
| Max. temperatura medija [°C] | 60 |
| D [mm] | 61.3 |
| B [mm] | 76.3 |
| Pretok [l/min] | 330 |