

Datum: 03.06.2026



Tlačni regulator »variobloc«, Velikost 1, G 3/8, 0.5 - 10 bar

Kategorija: [Pressure regulators, continuous pressure supply](#)Šifra: **100655RIE**

(slika je simbolična)

Kratek opis

Pressure regulator, continuous pressure supply »variobloc«, Size 1, G 3/8, Input pressure max. 25 bar, Control range 0.5 - 10 bar

Diaphragm pressure regulators with self-relieving design for mounting side by side. The pressure setting can be locked by pushing the knob down. By assembling two or more controllers together, it is possible to supply several working air circuits with different output pressures via a single supply line.

Tehnične Specifikacije

| | |
|------------------------------|---|
| Merjenje pretoka | At $P_1 = 10$ bar, $P_2 = 6$ bar and pressure drop $\Delta_p = 1$ bar |
| Navoj | G 3/8 |
| Ohišje | Die-cast zinc |
| Povezava zadaj | G 1/4 |
| Serija | variobloc |
| Tesnilo | NBR |
| Vzmet pokrova motorja | POM-brass |
| Min. krmilno območje [bar] | 0.5 |
| Velikost | 1 |
| Max. krmilno območje [bar] | 10 |
| Zaslon manometra max. [bar] | 10 |
| Max. vhodni tlak [bar] | 25 |
| C [mm] | 26.0 |
| A [mm] | 48.0 |
| Max. sobna temperatura [°C] | 80 |
| Max. temperatura medija [°C] | 80 |
| B [mm] | 98.0 |
| Pretok [l/min] | 1800 |