



Tlačni regulator »variobloc«, Velikost 2, G 3/4, 0.5 - 6 bar

Kategorija: [Pressure regulators](#)
Šifra: **100643RIE**

(slika je simbolična)

Kratek opis

Pressure regulator »variobloc«, incl. pressure gauge, Size 2, G 3/4, Input pressure max. 25 bar, Control range 0.5 - 6 bar Reversible diaphragm pressure regulators, independent of inlet pressure, with self-relieving design.

The pressure setting can be locked by pushing the knob down.

Approved series in modern industrial design, with the following key benefits:

- Simple handling
- Convenient modular assembly thanks to innovative fasteners
- Excellent flow values

Tehnične Specifikacije

| | |
|------------------------------|---|
| Membrane | NBR |
| Merjenje pretoka | At $P_1 = 10$ bar, $P_2 = 6$ bar and pressure drop $\Delta_p = 1$ bar |
| Navoj | G 3/4 |
| Ohišje | Die-cast zinc |
| Serija | variobloc |
| Tesnilo | NBR |
| Vzmet pokrova motorja | POM |
| Min. krmilno območje [bar] | 0.5 |
| Velikost | 2 |
| Max. krmilno območje [bar] | 6 |
| Zaslon manometra max. [bar] | 6 |
| Max. vhodni tlak [bar] | 25 |
| C [mm] | 33.0 |
| A [mm] | 70.0 |
| Max. sobna temperatura [°C] | 80 |
| Max. temperatura medija [°C] | 80 |
| B [mm] | 134.0 |
| Pretok [l/min] | 8000 |