



(slika je simbolična)

Tlačno stikalo, polikarbonat, Čep M8, 4-pol, G 1/8 ET, M5 IT

Kategorija: [Pressure switch](#)
Šifra: **108432RIE**

Kratek opis

Pressure switch, Polycarbonate, Plug M8, 4-pole, G 1/8 ET, M5 IT, M8x1 ET, Temperature 0 °C to 50 °C, 10.8 - 30 V DC
Universal electronic pressure switch for safety monitoring, optimisation of cycle times and regulation circuits. Its small size and low weight permit installation in handling systems directly at the point of use.

Tehnične Specifikacije

| | |
|--------------------------------|--|
| Električni priključek | Male connector M8, four pin |
| G 1 | G 1/8 ET |
| G 2 | M5 IT |
| G 3 | M8x1 ET |
| histereza | Adjustable: 0 to 100 % of set value or comparator mode |
| Izmerjena srednja povezava | G 1/8 ET and M5 IT |
| Ohišje | Polycarbonate |
| Srednje | Non-aggressive gases, dry, oil-free air |
| Vrsta gradnje | PNP |
| izhodni signal | 2 x digital |
| Navedba | 2 x LED |
| Izpis izmerjene vrednosti | 3-digit 7-segment LED |
| Merilno območje max. bar | 10 |
| Operativna napetost | 10.8 to 30 V DC |
| Max. temperaturno območje [°C] | 50 |
| Trenutna poraba [mA] | 55 |
| L [mm] | 58.5 |
| L1 [mm] | 75.5 |
| Preklopna zmogljivost | 180 mA |