



(slika je simbolična)

## Tlačno stikalo, zamenljiv kontakt, specialna zlitina, 0.5-8 bar

Kategorija: [Pressure switch, electrical connection M12x1](#)  
Šifra: **103034RIE**

### Kratek opis

Pressure switch, Electr. connection M12x1, Changeover contact, Special die casting, Temperature -20 °C to 80°C, G 1/4, 0.5 - 8 bar

For converting pneumatic to electrical signals.

Designed for use in rough vacuum applications (technical vacuum). Universal switch type, suitable as NC, NO or changeover contact. These devices are free from paint-wetting impairment substances (PWIS).

### Tehnične Specifikacije

Min. temperaturno območje [°C]	-20
Aplikacije	Pneumatic applications
Gumb za prilagajanje	Aluminium, powder-coated
IP zaščita	IP65 (DIN 43650), IP67 (M12x1)
Membrane	NBR
Ohišje	Special die-cast material
Povezava	G 1/4
Tesnilo	NBR
Min. prilagoditveno območje [bar]	0.5
Max. območje nastavitve [bar]	8
B [mm]	28.0
A [mm]	48.0
Preklopna napetost	48 V AC / 28 V DC
Max. temperaturno območje [°C]	80
Preklopna frekvenca	200/min.