

Datum: 01.07.2026



(slika je simbolična)

## Trojna Hitre spojke I.D. 7.2, G 1/4 notranji navoj

Kategorija: [Distributor, 3 quick disconnect coupl. DN 7.2, IT](#)  
Šifra: **107267RIE**

### Kratek opis

Distributor with 3 quick-connect couplings I.D. 7.2, Bright brass, G 1/4 IT, Operating pressure 0-35 bar, Temp. -20 °C to 100 °C

1, 2 or 3-way distributor pieces made of brass with a bare metal surface, pre-assembled with quick disconnect coupling DN 7.2.

Available with threaded connection inside or outside or nipple for adaptation into an existing quick disconnect coupling DN 7.2 to DN 7.8.

### Tehnične Specifikacije

|                              |   |
|------------------------------|---|
| Min. sobna temperatura [°C]  | -20   |
| Min. temperatura medija [°C] | -20   |
| Ohišje                       | Brass with a bare metal surface                   |
| Povezava                     | G 1/4 IT  |
| Sestava distributerja        | Brass with a bare metal surface, G 3/8 IT         |
| Spojke                       | DN 7.2, brass with a bare metal surface, G 3/8 ET |
| Tesnilo                      | Industrial adhesives, medium strength             |
| Varovaka                     | Industrial adhesives, medium strength             |
| Max. obratovalni tlak [bar]  | 35  |
| Višina [mm]                  | 96.0  |
| Max. sobna temperatura [°C]  | 100   |
| Max. temperatura medija [°C] | 100   |
| Premer [mm]                  | 115.0   |