

Datum: 13.03.2026



(slika je simbolična)

## Trojna Hitre spojke I.D. 7.2, G 1/4 notranji navoj

Kategorija: [Distributor, 3 quick disconnect coupl. DN 7.2, IT](#)  
Šifra: **107267RIE**

### Kratek opis

Distributor with 3 quick-connect couplings I.D. 7.2, Bright brass, G 1/4 IT, Operating pressure 0-35 bar, Temp. -20 °C to 100 °C

1, 2 or 3-way distributor pieces made of brass with a bare metal surface, pre-assembled with quick disconnect coupling DN 7.2.

Available with threaded connection inside or outside or nipple for adaptation into an existing quick disconnect coupling DN 7.2 to DN 7.8.

### Tehnične Specifikacije

Min. sobna temperatura [°C]	-20
Min. temperatura medija [°C]	-20
Ohišje	Brass with a bare metal surface
Povezava	G 1/4 IT
Sestava distributerja	Brass with a bare metal surface, G 3/8 IT
Spojke	DN 7.2, brass with a bare metal surface, G 3/8 ET
Tesnilo	Industrial adhesives, medium strength
Varovaka	Industrial adhesives, medium strength
Max. obratovalni tlak [bar]	35
Višina [mm]	96.0
Max. sobna temperatura [°C]	100
Max. temperatura medija [°C]	100
Premer [mm]	115.0