TRG d.o.o.
Celovška cesta 150, 1000 Ljubljana

Davčna št.: SI 56119488
Telefon: 01 500 14 42
E-mail: info@podjetje-trg.si
WWW: www.www.karcher-trg.si

Datum: 21.11.2026

Universal junction socket, 2 safety couplings I.D.7.4, input G1/2



(slika je simbolična)

Kategorija: Universal junction socket,2safety couplingsI.D.7.4
Šifra: **205213RIE**

Kratek opis

Universal junction socket, 2safety couplings I.D.7.4,inputG1/2,Op.pressure max.12bar,temp.air -10°C to 50°C,temp.water 1°C to 50°C
Do you like to use the devices more versatile instead of unilaterally? Universal distributor sockets support you in this.
• Vertical and horizontal use.
Connect workplaces of several levels over one another and next to one another. This directs your media in a direct path to the required delivery point.
• Safety via well thought out connection brackets.
The side connection is at a 90 ° angle. Mount your service units, consumers and pipes simply directly on the wall. Escape and transport routes remain clear.
• Flexible use.
The six connection options – 2 x front, 2 x side, 1 x above, 1 x below – offer the maximum flexibility of use.
• Available with or without couplings.
2 or 3-way distributor sockets made of high-strength glass fibre-reinforced plastic (PA6 GF 30) for a wide range of applications. All distributor sockets have a durable brass threaded insert, whose shape secures it against rotation and against axial shift due to its shape. Drilling diagram dimensions are identical for all distributor sockets, so a simpler and more flexible exchange replacement. Caution: Note that the distributor sockets should not be installed in danges zones. Danger zones are, for example, transport routes, escape routes, etc.

Tehnične Specifikacije

Min. delovna temperatura v zraku [°C]	-10
Dovodni navoj	G 1/2
Ohišje	Glass fibre-reinforced plastic PA6 GF 30
Min. delovna temperatura v vodi [°C]	1
Spojka	2 x Safety coupling
Max. moment privijanja - pritrdilne luknje [Nm]	4
Max. moment privijanja - medeninasta nit [Nm]	12
Max. obratovalni tlak [bar]	12
Max. delovna temperatura v vodi [°C]	50
Max. delovna temperatura v zraku [°C]	50
Višina [mm]	60.0
Premer [mm]	86.0