

Datum: 19.09.2024

Davčna št.: SI 56119488  
Telefon: 01 500 14 42  
E-mail: [info@podjetje-trg.si](mailto:info@podjetje-trg.si)  
WWW: [www.karcher-trg.si](http://www.karcher-trg.si)



(slika je simbolična)

## Varn. ventil, med., G 1/2, vkl. prit. 0.3 bar

Kategorija: [Varnostni ventil G 1/2](#)

Šifra: **104800RIE**

### Kratek opis

Safety valve, High performance design, Brass, Operating temp. -40 °C to 200 °C, G 1/2, AF 27, Trigger pressure 0.3 bar

For compressed air and non-toxic, non-flammable gases, cannot be used for liquids due to free blow-off, not suitable for steam.

These valves are TÜV approved and have a TÜV type test number.

### Tehnične Specifikacije

Min. delovna temperatura [°C]	-40
Navoj	G 1/2
Ohišje	Brass
Tesnilo	FPM
Tlačna vzmet	C steel
Min. nastavljeni tlak [bar]	0.3
Min. obratovalni tlak [bar]	0.5
narediti [mm]	12.0
A [mm]	14.0
Max. obratovalni tlak [bar]	26
a/f [mm]	27
H [mm]	93.0
Max. delovna temperatura [°C]	200