

Datum: 04.05.2026

Davčna št.: SI 56119488  
Telefon: 01 500 14 42  
E-mail: [info@podjetje-trg.si](mailto:info@podjetje-trg.si)  
WWW: [www.karcher-trg.si](http://www.karcher-trg.si)



(slika je simbolična)

## Varn. ventil, med., G 3/4, vkl. prit. 14 bar

Kategorija: [Varnostni ventil G 3/4](#)  
Šifra: **104898RIE**

### Kratek opis

Safety valve, High performance design, Brass, Operating temp. -40 °C to 200 °C, G 3/4, AF 32, Trigger pressure 14 bar  
For compressed air and non-toxic, non-flammable gases, cannot be used for liquids due to free blow-off, not suitable for steam.  
These valves are TÜV approved and have a TÜV type test number.

### Tehnične Specifikacije

Min. delovna temperatura [°C]	-40
Navoj	G 3/4
Ohišje	Brass
Tesnilo	FPM
Tlačna vzmet	C steel
Min. obratovalni tlak [bar]	0.5
Min. nastavljeni tlak [bar]	14
narediti [mm]	15.0
A [mm]	16.0
Max. obratovalni tlak [bar]	26
a/f [mm]	32
H [mm]	110.0
Max. delovna temperatura [°C]	200