

Datum: 27.06.2026

Davčna št.: SI 56119488  
Telefon: 01 500 14 42  
E-mail: [info@podjetje-trg.si](mailto:info@podjetje-trg.si)  
WWW: [www.karcher-trg.si](http://www.karcher-trg.si)



(slika je simbolična)

## Varn.ventil s pol. hod. DN 10, G 1/2, vkl. prit. 33 bar

Kategorija: [Varnostni ventil G 1/2](#)  
Šifra: **104651RIE**

### Kratek opis

Full stroke safety valve DN 10, Brass, Operating temp. -25 °C to 180 °C, G 1/2, AF 27, Trigger pressure 33 bar, Type tested  
For compressed air and non-toxic, non-flammable gases, cannot be used for liquids due to free blow-off, not suitable for steam.  
These valves are TÜV approved and have a TÜV type test number.

### Tehnične Specifikacije

Min. delovna temperatura [°C]	-25
Navoj	G 1/2
Ohišje	Brass
Tesnilo	FKM
Tlačna vzmet	Stainless steel
Min. obratovalni tlak [bar]	0.2
D [mm]	14.0
A [mm]	26.0
a/f [mm]	27
Min. nastavljeni tlak [bar]	33
Max. obratovalni tlak [bar]	50
C [mm]	95.0
Max. delovna temperatura [°C]	180