

Datum: 21.06.2026

Davčna št.: SI 56119488  
Telefon: 01 500 14 42  
E-mail: [info@podjetje-trg.si](mailto:info@podjetje-trg.si)  
WWW: [www.karcher-trg.si](http://www.karcher-trg.si)

(slika je simbolična)

## Varn.ventil s pol. hod. DN 8, G 1/4, vkl. prit. 42 bar

Kategorija: [Varnostni ventil G 1/4](#)  
Šifra: **104094RIE**

### Kratek opis

Full stroke safety valve DN 8, Brass, Operating temperature -25 °C to 180 °C, G 1/4, AF 20, Trigger pressure 42 bar, Type tested  
For compressed air and non-toxic, non-flammable gases, cannot be used for liquids due to free blow-off, not suitable for steam.  
These valves are TÜV approved and have a TÜV type test number.

### Tehnične Specifikacije

Min. delovna temperatura [°C]	-25
Navoj	G 1/4
Ohišje	Brass
Tesnilo	FKM
Tlačna vzmet	Stainless steel
Min. obratovalni tlak [bar]	0.2
D [mm]	10.0
A [mm]	18.0
a/f [mm]	20
Min. nastavljeni tlak [bar]	42
Max. obratovalni tlak [bar]	50
C [mm]	82.0
Max. delovna temperatura [°C]	180