TRG d.o.o.
Celovška cesta 150, 1000 Ljubljana

Davčna št.: SI 56119488
Telefon: 01 500 14 42
E-mail: info@podjetje-trg.si
WWW: www.www.karcher-trg.si

Datum: 11.11.2026



(slika je simbolična)

Varnostna čeljustna spojka z notranjim navojem, G 3/4, DN 17

Kategorija: Safety claw coupling, female threaded
Šifra: **107881RIE**

Kratek opis

Safety jaw coupling with interior thread, G 3/4, DN 17, Malleable cast iron, Operating pressure max. 16 bar, Temp. -40°C to 95°C
Universal standard coupling in safety design according to DIN 3238 for absolutely secure compressed air lines on construction sites or in industry.
Easy to couple, secured against accidental opening: just screw the ring tight after coupling!
- Robust couplings with malleable iron head, steel stem with special profile,
zinc plated and yellow chromated
- Chrome VI-free, with double safety lock
- Large bore for increased flow rate

Tehnične Specifikacije

Min. delovna temperatura [°C]	-40
Material	Malleable iron
Navoj	G 3/4
Tesnilo	NBR
Max. obratovalni tlak [bar]	16
DN	17
a/f [mm]	32
Razdalja med objemkami [mm]	42
H [mm]	63.0
L [mm]	90.2
Max. delovna temperatura [°C]	95