

Datum: 31.05.2026

Davčna št.: SI 56119488
Telefon: 01 500 14 42
E-mail: info@podjetje-trg.si
WWW: www.karcher-trg.si



Varnostna čeljustna spojka z notranjim navojem, G 3/4, DN 17

Kategorija: [Safety claw coupling, female threaded](#)
Šifra: **107881RIE**

(slika je simbolična)

Kratek opis

Safety jaw coupling with interior thread, G 3/4, DN 17,
Malleable cast iron, Operating pressure max. 16 bar, Temp.
-40°C to 95°C

Universal standard coupling in safety design according to
DIN 3238 for absolutely secure compressed air lines on
construction sites or in industry.

Easy to couple, secured against accidental opening: just
screw the ring tight after coupling!

- Robust couplings with malleable iron head, steel stem with special profile, zinc plated and yellow chromated
- Chrome VI-free, with double safety lock
- Large bore for increased flow rate

Tehnične Specifikacije

Min. delovna temperatura [°C]	-40
Material	Malleable iron
Navoj	G 3/4
Tesnilo	NBR
Max. obratovalni tlak [bar]	16
DN	17
a/f [mm]	32
Razdalja med objemkami [mm]	42
H [mm]	63.0
L [mm]	90.2
Max. delovna temperatura [°C]	95