

Datum: 10.05.2026

Davčna št.: SI 56119488
Telefon: 01 500 14 42
E-mail: info@podjetje-trg.si
WWW: www.karcher-trg.si



(slika je simbolična)

Varnostna čeljustna spojka z zunanjim navojem, G 3/4, DN 17

Kategorija: [Safety claw coupling, male threaded](#)
Šifra: **107877RIE**

Kratek opis

Safety jaw coupling with exterior thread, G 3/4, DN 17,
Malleable cast iron, Operating pressure max. 16 bar, Temp.
-40°C to 95°C

Universal standard coupling in safety design according to
DIN 3238 for absolutely secure compressed air lines on
construction sites or in industry.

Easy to couple, secured against accidental opening: just
screw the ring tight after coupling!

- Robust couplings with malleable iron head, steel stem with special profile, zinc plated and yellow chromated
- Chrome VI-free, with double safety lock
- Large bore for increased flow rate

Tehnične Specifikacije

| | |
|-------------------------------|----------------|
| Min. delovna temperatura [°C] | -40 |
| Material | Malleable iron |
| Navoj | G 3/4 |
| Tesnilo | NBR |
| Max. obratovalni tlak [bar] | 16 |
| DN | 17 |
| a/f [mm] | 24 |
| Razdalja med objemkami [mm] | 42 |
| H [mm] | 63.0 |
| L [mm] | 70.2 |
| Max. delovna temperatura [°C] | 95 |