

Datum: 11.07.2026

Davčna št.: SI 56119488  
Telefon: 01 500 14 42  
E-mail: [info@podjetje-trg.si](mailto:info@podjetje-trg.si)  
WWW: [www.karcher-trg.si](http://www.karcher-trg.si)



(slika je simbolična)

## Varnostna čeljustna spojka z zunanjim navojem, G 3/4, DN 17

Kategorija: [Safety claw coupling, male threaded](#)  
Šifra: **107877RIE**

### Kratek opis

Safety jaw coupling with exterior thread, G 3/4, DN 17,  
Malleable cast iron, Operating pressure max. 16 bar, Temp.  
-40°C to 95°C

Universal standard coupling in safety design according to  
DIN 3238 for absolutely secure compressed air lines on  
construction sites or in industry.

Easy to couple, secured against accidental opening: just  
screw the ring tight after coupling!

- Robust couplings with malleable iron head, steel stem with special profile, zinc plated and yellow chromated
- Chrome VI-free, with double safety lock
- Large bore for increased flow rate

### Tehnične Specifikacije

Min. delovna temperatura [°C]	-40
Material	Malleable iron
Navoj	G 3/4
Tesnilo	NBR
Max. obratovalni tlak [bar]	16
DN	17
a/f [mm]	24
Razdalja med objemkami [mm]	42
H [mm]	63.0
L [mm]	70.2
Max. delovna temperatura [°C]	95