

Datum: 13.05.2026

Davčna št.: SI 56119488  
Telefon: 01 500 14 42  
E-mail: [info@podjetje-trg.si](mailto:info@podjetje-trg.si)  
WWW: [www.karcher-trg.si](http://www.karcher-trg.si)



(slika je simbolična)

## Varnostni krogelni ventil, z zaklepom, brez izpustom, Rp 3/8

Kategorija: [Safety ball valves, lockable, without relief port](#)  
Šifra: **103142RIE**

### Kratek opis

Safety ball valve, lockable, without venting hole, nickel-plated brass, Operating temp. max. 170°C, Rp 3/8, DN 10, PN max. 65 bar  
2/2-way safety ball valves made of nickel-plated brass.  
The ball valve can be locked manually.  
Full bore, heavy-duty type.

### Tehnične Specifikacije

Min. delovna temperatura [°C]	-40
Bore diameter padlock	ca. 7.4 mm
Krogelno tesnilo	PTFE
Material	Nickel-plated brass
Material navojev	Nickel-plated brass
Navoj	Rp 3/8
Ročica	Steel - PVC coated
Standardni navoj	Rp thread acc. to EN 10226
Stebelno tesnilo	PTFE
DN	10
B [mm]	39.5
L [mm]	51.0
PN [bar]	65
A [mm]	82.0
Max. delovna temperatura [°C]	170