



(slika je simbolična)

Varnostni krogelni ventil, z zaklepom, z izpustom, Rp 1

Kategorija: [Safety ball valves, lockable, with relief port](#)
Šifra: **103153RIE**

Kratek opis

Safety ball valve, lockable, Venting hole M5, nickel-plated brass, Operating temp. -10 °C to 100 °C, Rp 1, DN 25, PN max. 14 bar
Safety ball valves, two parts, made of nickel-plated brass. Specially designed for pneumatic applications.
The valve shuts off the supply line and bleds the application area.
Lockable hand lever in closed position ensures a high protection against manipulation.

Tehnične Specifikacije

Min. delovna temperatura [°C]	-10
Bore diameter padlock	ca. 7.3 mm
Izpušni vtič	M5
Krogelno tesnilo	PTFE
Krogla	Chrome-plated brass
Material navojev	Nickel-plated brass
Navoj	Rp 1
Ohišje	Nickel-plated brass
Ročica	Steel - PVC coated
Standardni navoj	Rp thread acc. to EN 10226
Stebelno tesnilo	FKM
Max. obratovalni tlak [bar]	14
DN	25
B [mm]	64.0
L [mm]	81.0
Max. delovna temperatura [°C]	100
A [mm]	117.0