

Datum: 20.04.2026

Davčna št.: SI 56119488  
Telefon: 01 500 14 42  
E-mail: [info@podjetje-trg.si](mailto:info@podjetje-trg.si)  
WWW: [www.karcher-trg.si](http://www.karcher-trg.si)



(slika je simbolična)

## Ventil za zmanjšanje tlaka, G 1/4 i. / o., Nastavitveni tlak 5 bar

Kategorija: [Pressure reducing valves](#)  
Šifra: **101512RIE**

### Kratek opis

Pressure reducing valve, G 1/4 interior / exterior, AF 17, Set pressure 5 bar, Input pressure max. 15 bar, Material: Brass  
Industry, trade and repair shops often require working pressures of 15 bar or less.

These pressure reducing valves, which are screwed directly onto the tool, enable that the pressure can be reduced to the selected working pressure.

Benefits:

- Significantly reduced risk of accidents
- Longer tool life with fewer malfunctions
- Lower noise levels at the workplace

### Tehnične Specifikacije

Ohišje	Brass
Priključni navoj	G 1/4 female / male
Nastavitev tlaka [bar]	5
B [mm]	9.0
Max. vhodni tlak [bar]	15
a/f [mm]	17
C Ø [mm]	17.0
A [mm]	34.0
Pretok [l/min]	390