

Datum: 02.05.2025

Davčna št.: SI 56119488
Telefon: 01 500 14 42
E-mail: info@podjetje-trg.si
WWW: www.karcher-trg.si



Visoko zmogl. varnos.ventil, G 1 1/4, vkl. prit. 11.5 bar

Kategorija: [High-pressure Varnostni ventil G 1 1/4](#)
Šifra: **105316RIE**

(slika je simbolična)

Kratek opis

High performance safety valve, Vibration-proof design, Brass, Operating temp. max 260°C, G 1 1/4, AF 50, Trigger pressure 11.5 bar
Proportional, spring-loaded safety valves with a lifting device. Type-tested acc. to VdTÜV Specification for safety valves 100.
Exceptionally reliable, even when installed in extreme environments (vibration-resistant design).
Suitable for compressed air and other non-toxic, neutral and non-flammable gases that may be freely released. Not suitable for steam.

Tehnične Specifikacije

Navoj	G 1 1/4
Ohišje	Brass
Vzmet pokrova motorja	Malleable iron, powder-coated blue
Min. obratovalni tlak [bar]	0.5
Min. nastavljeni tlak [bar]	11.5
A [mm]	18.0
narediti [mm]	25.0
Max. obratovalni tlak [bar]	30
a/f [mm]	50
H [mm]	231.0
Max. delovna temperatura [°C]	260