

Datum: 21.04.2026

(slika je simbolična)

Visoko zmogl. varnos.ventil, G 1, vkl. prit. 28 bar

Kategorija: [High-pressure Varnostni ventil G 1](#)
Šifra: **105283RIE**

Kratek opis

High performance safety valve, Vibration-proof design, Brass, Operating temp. max. 260 °C, G 1, AF 41, Trigger pressure 28 bar
Proportional, spring-loaded safety valves with a lifting device. Type-tested acc. to VdTÜV Specification for safety valves 100.
Exceptionally reliable, even when installed in extreme environments (vibration-resistant design).
Suitable for compressed air and other non-toxic, neutral and non-flammable gases that may be freely released. Not suitable for steam.

Tehnične Specifikacije

| | |
|-------------------------------|-------|
| Navoj | G 1 |
| Ohišje | Brass |
| Vzmet pokrova motorja | Brass |
| Min. obratovalni tlak [bar] | 0.5 |
| A [mm] | 16.0 |
| narediti [mm] | 20.0 |
| Min. nastavljeni tlak [bar] | 28 |
| Max. obratovalni tlak [bar] | 30 |
| a/f [mm] | 41 |
| H [mm] | 185.0 |
| Max. delovna temperatura [°C] | 260 |