

Datum: 13.06.2026



Visoko zmogl. varnos.ventil, G 1/2, vkl. prit. 17 bar

Kategorija: [High-pressure Varnostni ventil G 1/2](#)
Šifra: **105140RIE**

(slika je simbolična)

Kratek opis

High performance safety valve, Vibration-proof design, Brass, Operating temp. max. 260 °C, G 1/2, AF 27, Trigger pressure 17 bar

Proportional, spring-loaded safety valves with a lifting device. Type-tested acc. to VdTÜV Specification for safety valves 100.

Exceptionally reliable, even when installed in extreme environments (vibration-resistant design).

Suitable for compressed air and other non-toxic, neutral and non-flammable gases that may be freely released. Not suitable for steam.

Tehnične Specifikacije

| | |
|-------------------------------|-------|
| Navoj | G 1/2 |
| Ohišje | Brass |
| Vzmet pokrova motorja | Brass |
| Min. obratovalni tlak [bar] | 0.5 |
| narediti [mm] | 10.0 |
| A [mm] | 12.0 |
| Min. nastavljeni tlak [bar] | 17 |
| a/f [mm] | 27 |
| Max. obratovalni tlak [bar] | 30 |
| H [mm] | 138.0 |
| Max. delovna temperatura [°C] | 260 |