

Datum: 09.10.2025

Davčna št.: SI 56119488
Telefon: 01 500 14 42
E-mail: info@podjetje-trg.si
WWW: www.karcher-trg.si



(slika je simbolična)

Visoko zmogl. varnos.ventil, G 1/2, vkl. prit. 7 bar

Kategorija: [High-pressure Varnostni ventil G 1/2](#)
Šifra: **105115RIE**

Kratek opis

High performance safety valve, Vibration-proof design, Brass, Operating temp. max. 260 °C, G 1/2, AF 27, Trigger pressure 7 bar

Proportional, spring-loaded safety valves with a lifting device. Type-tested acc. to VdTÜV Specification for safety valves 100.

Exceptionally reliable, even when installed in extreme environments (vibration-resistant design).

Suitable for compressed air and other non-toxic, neutral and non-flammable gases that may be freely released. Not suitable for steam.

Tehnične Specifikacije

Navoj	G 1/2
Ohišje	Brass
Vzmet pokrova motorja	Brass
Min. obratovalni tlak [bar]	0.5
Min. nastavljeni tlak [bar]	7
narediti [mm]	10.0
A [mm]	12.0
a/f [mm]	27
Max. obratovalni tlak [bar]	30
H [mm]	138.0
Max. delovna temperatura [°C]	260