



(slika je simbolična)

Visoko zmogljiv tlačni regulator, G 2, 0.5 - 16 bar

Kategorija: [Heavy-duty pressure regulators](#)
Šifra: **101266RIE**

Kratek opis

High performance pressure regulator with 2 pressure gauges, G 2, Control range 0.5 - 16 bar, Input pressure max. 25 bar
Diaphragm pressure regulators, independent of inlet pressure, with internal pilot control and self-relieving design for very high flow rates.
Separate indication of input and working pressure on two pressure gauges.
The pressure setting can be locked by pushing the knob down.

Tehnične Specifikacije

| | |
|------------------------------|--|
| Merjenje pretoka | At $P_1 = 8$ bar, $P_2 = 6$ bar and pressure drop $\Delta_p = 1$ bar |
| Navoj | G 2 |
| Ohišje | Aluminium, painted silver |
| Tesnilo | NBR |
| Min. krmilno območje [bar] | 0.5 |
| Max. krmilno območje [bar] | 16 |
| Max. vhodni tlak [bar] | 25 |
| Zaslon manometra max. [bar] | 25 |
| DN | 50 |
| Max. sobna temperatura [°C] | 60 |
| Max. temperatura medija [°C] | 60 |
| A [mm] | 160.0 |
| B [mm] | 261.0 |
| Pretok | 50000 l/min |