

Datum: 26.04.2026



Visokotlačni reg. 60 barG 1Regulacijsko območje 3 - 50 bar

Kategorija: [High pressure regulators up to 60 bar](#)Šifra: **101154RIE**

(slika je simbolična)

Kratek opis

High pressure regulator 60 bar, G 1, Control range 3 - 50 bar, Input pressure max. 60 bar, Operating temp. -10 °C to 90 °C

Reversible piston-type pressure regulator, virtually independent of inlet pressure, with self-relieving design, manufactured entirely in brass.

Specially designed for high pressures up to 60 bar. Pressure catch with counter nut.

Tehnične Specifikacije

| | |
|-------------------------------|---|
| Min. delovna temperatura [°C] | -10 |
| Aplikacije | Compressed air and other neutral, non-flammable gases At $P_1 = 20$ bar, $P_2 = 10$ bar and pressure drop $\Delta_p = 4$ bar |
| Merjenje pretoka | |
| Navoj | G 1 |
| Ohišje | Brass |
| Tesnilo | NBR |
| Min. krmilno območje [bar] | 3 |
| Max. krmilno območje [bar] | 50 |
| C [mm] | 51.0 |
| Max. vhodni tlak [bar] | 60 |
| Max. delovna temperatura [°C] | 90 |
| A [mm] | 118.0 |
| D [mm] | 206.0 |
| B [mm] | 257.0 |
| Pretok [l/min] | 5000 |