



Visokotlačni reg. 60 barG 3/8Regulacijsko območje 2 - 50 bar

Kategorija: [High pressure regulators up to 60 bar](#)
Šifra: **101150RIE**

(slika je simbolična)

Kratek opis

High pressure regulator 60 bar, G 3/8, Control range 2 - 50 bar, Input pressure max. 60 bar, Operating temp. -10 °C to 90 °C

Reversible piston-type pressure regulator, virtually independent of inlet pressure, with self-relieving design, manufactured entirely in brass.

Specially designed for high pressures up to 60 bar. Pressure catch with counter nut.

Tehnične Specifikacije

| | |
|-------------------------------|---|
| Min. delovna temperatura [°C] | -10 |
| Aplikacije | Compressed air and other neutral, non-flammable gases At $P_1 = 20$ bar, $P_2 = 10$ bar and pressure drop $\Delta p = 4$ bar |
| Merjenje pretoka | |
| Navoj | G 3/8 |
| Ohišje | Brass |
| Tesnilo | NBR |
| Min. krmilno območje [bar] | 2 |
| C [mm] | 31.0 |
| Max. krmilno območje [bar] | 50 |
| Max. vhodni tlak [bar] | 60 |
| A [mm] | 72.0 |
| Max. delovna temperatura [°C] | 90 |
| D [mm] | 133.0 |
| B [mm] | 164.0 |
| Pretok [l/min] | 2500 |