

Datum: 10.05.2026

Davčna št.: SI 56119488
Telefon: 01 500 14 42
E-mail: info@podjetje-trg.si
WWW: www.karcher-trg.si



Vitel za gibko cev, PU proti prisilni., Fi9.5x13.5, dolžina 14 m

Kategorija: [Hose reels for compressed air, anti-spark](#)
Šifra: **136360RIE**

(slika je simbolična)

Kratek opis

Hose reel for compressed air, PU, anti-spark, Hose- \emptyset 9.5x13.5, Length 14 m, Operating temp. -20 °C to 60 °C, PN max. 12 bar

For simple mounting on the wall or ceiling.

Shock resistant, solid and closed housing made of POM, disposal/outflow R 1/4 AG and with light, heavy duty, oil resistant and spark erosion protected polyurethane hose.

The hose is resistant to flying sparks and scorching, which can occur in the welding environment or with the use of cutting tools.

Incl. 2 m supply hose.

Tehnične Specifikacije

Min. delovna temperatura [°C]	-20
Aplikacije	for compressed air braided, spark erosion protected
Material cevi	polyurethane
Velikost cevi [mm]	9.5x13.5
Max. obratovalni tlak [bar]	12
Dolžina cevi [m]	14
Max. delovna temperatura [°C]	60
Zasučni kot [°]	300
A [mm]	395.5
B [mm]	453.6