

Datum: 20.04.2026



(slika je simbolična)

## Vranostna vrtljiva spojka I.D. 6, ISO 6150 C, I.D. 10, rdeča

Kategorija: [Non-interchangeable swivel safety coupling, stem](#)  
Šifra: **141853RIE**

### Kratek opis

Captive swivel safety coupling I.D. 6, ISO 6150 C, Steel, 2-stage, Sleeve I.D. 10, red, max. 25 bar, Temp. -15 °C to 200 °C

High quality, robust and long lifetime one-hand rotation secure coupling.

A secure connection is made by pushing in the plug-in nipple that clicks in audibly. Uncoupling is done by rotating the sleeve anti-clockwise. For this, the pending pressure in the coupling and line are vented, however the plug-in nipple is not completely released via a safety latch.

The plug-in nipple can only be pulled out after a clockwise rotation of the sleeve. The colour and shape coding of the coupling and plug-in nipple makes it possible only to couple to the same colours.

This coupling meets ISO standard DIN EN ISO 4414, EN 983. Areas of application: Pneumatic system, machine and plant engineering, measurement, monitoring and control systems, manufacturing industry, workshops, automotive, mining.

### Tehnične Specifikacije

|                                |  |
|--------------------------------|--|
| Min. temperaturno območje [°C] | -15  |
| Barva                          | Red  |
| Delovni tlak                   | max. 25 bar / max. 16 bar when attaching / detaching |
| Merjenje pretoka               | at 6 bar and $\Delta p = 0.5$ bar                    |
| Navojni kos                    | Galvanised steel                                     |
| Ohišje                         | Steel, QPQ treated                                   |
| Povezava                       | I.D. 10  |
| Rokav                          | Galvanised steel, painted colored                    |
| Tesnilo                        | FKM  |
| Ventil                         | Polyphenylene sulfide (PPS)                          |
| Vtični profil                  | acc. ISO 6150 C                                      |
| Vzmet                          | Stainless steel                                      |
| DN                             | 6  |
| a/f [mm]                       | 22   |
| Dolžina [mm]                   | 75.0   |
| Max. temperaturno območje [°C] | 200  |
| Pretok                         | 630 l/min (air)                                      |