

Datum: 13.05.2026



(slika je simbolična)

Vranostna vrtljiva spojka I.D. 6, ISO 6150 C, I.D. 10, siva

Kategorija: [Non-interchangeable swivel safety coupling, stem](#)
Šifra: **141879RIE**

Kratek opis

Captive swivel safety coupling I.D. 6, ISO 6150 C, Steel, 2-stage, Sleeve I.D. 10, gray, max. 25 bar, Temp. -15 °C to 200 °C

High quality, robust and long lifetime one-hand rotation secure coupling.

A secure connection is made by pushing in the plug-in nipple that clicks in audibly. Uncoupling is done by rotating the sleeve anti-clockwise. For this, the pending pressure in the coupling and line are vented, however the plug-in nipple is not completely released via a safety latch.

The plug-in nipple can only be pulled out after a clockwise rotation of the sleeve. The colour and shape coding of the coupling and plug-in nipple makes it possible only to couple to the same colours.

This coupling meets ISO standard DIN EN ISO 4414, EN 983. Areas of application: Pneumatic system, machine and plant engineering, measurement, monitoring and control systems, manufacturing industry, workshops, automotive, mining.

Tehnične Specifikacije

| | |
|--------------------------------|----------------------------------------------------------------------------------------|
| Min. temperaturno območje [°C] | -15 |
| Barva | Gray |
| Delovni tlak | max. 25 bar / max. 16 bar when attaching / detaching at 6 bar and $\Delta_p = 0.5$ bar |
| Merjenje pretoka | Galvanised steel |
| Navojni kos | Steel, QPQ treated |
| Ohišje | I.D. 10 |
| Povezava | Galvanised steel, painted colored |
| Rokav | FKM |
| Tesnilo | Polyphenylene sulfide (PPS) |
| Ventil | acc. ISO 6150 C |
| Vtični profil | Stainless steel |
| Vzmet | 6 |
| DN | 22 |
| a/f [mm] | 75.0 |
| Dolžina [mm] | 200 |
| Max. temperaturno območje [°C] | 630 l/min (air) |
| Pretok | |