

Datum: 13.05.2026



(slika je simbolična)

## Vranostna vrtljiva spojka I.D. 6, ISO 6150 C, I.D. 8, siva

Kategorija: [Non-interchangeable swivel safety coupling, stem](#)  
Šifra: **141878RIE**

### Kratek opis

Captive swivel safety coupling I.D. 6, ISO 6150 C, Steel, 2-stage, Sleeve I.D. 8, gray, max. 25 bar, Temp. -15 °C to 200 °C

High quality, robust and long lifetime one-hand rotation secure coupling.

A secure connection is made by pushing in the plug-in nipple that clicks in audibly. Uncoupling is done by rotating the sleeve anti-clockwise. For this, the pending pressure in the coupling and line are vented, however the plug-in nipple is not completely released via a safety latch.

The plug-in nipple can only be pulled out after a clockwise rotation of the sleeve. The colour and shape coding of the coupling and plug-in nipple makes it possible only to couple to the same colours.

This coupling meets ISO standard DIN EN ISO 4414, EN 983. Areas of application: Pneumatic system, machine and plant engineering, measurement, monitoring and control systems, manufacturing industry, workshops, automotive, mining.

### Tehnične Specifikacije

Min. temperaturno območje [°C]	-15
Barva	Gray
Delovni tlak	max. 25 bar / max. 16 bar when attaching / detaching at 6 bar and $\Delta_p = 0.5$ bar
Merjenje pretoka	at 6 bar and $\Delta_p = 0.5$ bar
Navojni kos	Galvanised steel
Ohišje	Steel, QPQ treated
Povezava	I.D. 8
Rokav	Galvanised steel, painted colored
Tesnilo	FKM
Ventil	Polyphenylene sulfide (PPS)
Vtični profil	acc. ISO 6150 C
Vzmet	Stainless steel
DN	6
a/f [mm]	22
Dolžina [mm]	75.0
Max. temperaturno območje [°C]	200
Pretok	630 l/min (air)