

Datum: 27.06.2026

Davčna št.: SI 56119488  
Telefon: 01 500 14 42  
E-mail: [info@podjetje-trg.si](mailto:info@podjetje-trg.si)  
WWW: [www.karcher-trg.si](http://www.karcher-trg.si)



(slika je simbolična)

## Vtični-L fitting »Click-klak«, vrtljivi, G 1/8 o.

Kategorija: [Male elbow, swivel type, parallel ET with O-ring](#)  
Šifra: **108597RIE**

### Kratek opis

Push-in L-fitting »click-clock«, rotating, G 1/8 o., for hose exterior Ø 4, Working pressure -0.99 to 16 bar, nickel-plated brass

The advanced version of our highly successful push-in fittings series manufactured in nickel-plated brass.

Advantages of this new, optimised series:

- Much easier connection and disconnection of the hose, even with repeated mounting
- Can also be used for non-calibrated hoses
- Suitable for vacuum operation

### Tehnične Specifikacije

Min. delovna temperatura [°C]	-20
Min. delovni tlak [bar]	-0.99
Material	Nickel-plated brass
Navoj	G 1/8
Priporočena cev	PA, PU
Rokav	Hostaform
Serija	click-clock
Vpenjalni obroč	Stainless steel
Za cevi O.D. [mm]	4
a/f [mm]	12
Max. delovni tlak [bar]	16
L1 [mm]	18.6
L2 [mm]	19.1
Max. delovna temperatura [°C]	80