

Datum: 09.06.2026

Davčna št.: SI 56119488  
Telefon: 01 500 14 42  
E-mail: [info@podjetje-trg.si](mailto:info@podjetje-trg.si)  
WWW: [www.karcher-trg.si](http://www.karcher-trg.si)



(slika je simbolična)

## Vtični-L fitting Metallice vrt., G 1/8 , cev Ø 4

Kategorija: [Male elbow, swivel type, parallel ET with O-ring](#)  
Šifra: **108896RIE**

### Kratek opis

Push-in L-fitting »metallica«, rotating, G 1/8 o., for hose exterior Ø 4, Working pressure -0.98 to 16 bar, nickel-plated brass

All parts with a parallel thread are supplied with an FPM O-ring while the conical threads are coated with preCOTE 5 dispersion

### Tehnične Specifikacije

Min. delovna temperatura [°C]	-20
Min. delovni tlak [bar]	-0.98
Material	Nickel-plated brass
Navoj	G 1/8
Priporočena cev	PA and PU
Rokav	Nickel-plated brass
Serijska	metallica
Vpenjalni obroč	Male elbow, swivel type, parallel male thread with O-ring (FPM)
Za cevi O.D. [mm]	4
a/f [mm]	13
Max. delovni tlak [bar]	16
L1 [mm]	20.0
L2 [mm]	20.0
Max. delovna temperatura [°C]	150