

Datum: 09.06.2026

Davčna št.: SI 56119488
Telefon: 01 500 14 42
E-mail: info@podjetje-trg.si
WWW: www.karcher-trg.si



Vtični L nast., vrtljiv, G 1/4 , zun. premera 10 mm

Kategorija: [Run tee, swivel type, parallel male thread, O-ring](#)
Šifra: **110385RIE**

(slika je simbolična)

Kratek opis

Push-in L-fitting, rotating, G 1/4 o., for hose exterior Ø 10 mm, Working pressure max. 15 bar, Stainless steel 1.4404
For use with aggressive media and in areas susceptible to corrosive outside influences, in the food processing industry and in hygienic and sanitary applications.

Tehnične Specifikacije

| | |
|-------------------------------|---------------------------|
| Min. delovna temperatura [°C] | -20 |
| Min. temperatura medija [°C] | -20 |
| Material | Stainless steel 1.4404 |
| Navoj | G 1/4 |
| Primerni materiali za cevi | PVDF, PTFE, PA, PU |
| Standardni navoj | DIN EN ISO 228-1 |
| Delovni tlak pulzira [bar] | 10 |
| Za cevi O.D. [mm] | 10 |
| Max. delovni tlak [bar] | 15 |
| a/f [mm] | 16 |
| L2 [mm] | 22.5 |
| L1 [mm] | 25.5 |
| Max. delovna temperatura [°C] | 150 |
| Max. temperatura medija [°C] | 150 |