

Datum: 26.05.2026

Davčna št.: SI 56119488
Telefon: 01 500 14 42
E-mail: info@podjetje-trg.si
WWW: www.karcher-trg.si

Vtični L nast., vrtljiv, G 3/8 , zun. premera 12 mm



Kategorija: [Run tee, swivel type, parallel male thread, O-ring](#)
Šifra: **135134RIE**

(slika je simbolična)

Kratek opis

Push-in L-fitting, rotating, G 3/8 o., for hose exterior Ø 12 mm, Working pressure -0.98 - 20 bar, Stainless steel 1.4404
For use in more aggressive environments and corrosive media.

The suitability test for the individual application is the user's responsibility.

Tehnične Specifikacije

Min. delovna temperatura [°C]	-20
Min. temperatura medija [°C]	-20
Min. delovni tlak [bar]	-0.98
Material	Stainless steel 1.4404
Navoj	G 3/8
Primerni materiali za cevi	PVDF, PTFE, PA, PU
Standardni navoj	DIN EN ISO 228-1
Tesnilo	FPM
Za cevi O.D. [mm]	12
Max. delovni tlak [bar]	20
a/f [mm]	21
L1 [mm]	26.7
L2 [mm]	32.6
Max. delovna temperatura [°C]	150
Max. temperatura medija [°C]	150