

Datum: 19.04.2026

Davčna št.: SI 56119488
Telefon: 01 500 14 42
E-mail: info@podjetje-trg.si
WWW: www.karcher-trg.si



Vtični L nast., vrtljiv, R 1/4 , zun. premera 6 mm

Kategorija: [Run tee, swivel type, conical male thread](#)
Šifra: **135144RIE**

(slika je simbolična)

Kratek opis

Push-in L-fitting, rotating, R 1/4 o., for hose exterior Ø 6 mm,
Working pressure -0.98 - 20 bar, Stainless steel 1.4404
For use in more aggressive environments and corrosive
media.
The suitability test for the individual application is the user's
responsibility.

Tehnične Specifikacije

Min. delovna temperatura [°C]	-20
Min. temperatura medija [°C]	-20
Min. delovni tlak [bar]	-0.98
Material	Stainless steel 1.4404
Navoj	R 1/4
Primerni materiali za cevi	PVDF, PTFE, PA, PU
Standardni navoj	ISO 7-1
Za cevi O.D. [mm]	6
a/f [mm]	14
Max. delovni tlak [bar]	20
L1 [mm]	22.0
L2 [mm]	30.5
Max. delovna temperatura [°C]	150
Max. temperatura medija [°C]	150