

Datum: 18.04.2026

Davčna št.: SI 56119488
Telefon: 01 500 14 42
E-mail: info@podjetje-trg.si
WWW: www.karcher-trg.si



(slika je simbolična)

Vtični L nast., vrtljiv, R 1/8 , zun. premera 6 mm

Kategorija: [Run tee, swivel type, conical male thread](#)
Šifra: **110390RIE**

Kratek opis

Push-in L-fitting, rotating, R 1/8 o., for hose exterior Ø 6 mm,
Working pressure max. 15 bar, Stainless steel 1.4404
For use with aggressive media and in areas susceptible to
corrosive outside
influences, in the food processing industry and in hygienic
and sanitary applications.

Tehnične Specifikacije

Min. delovna temperatura [°C]	-20
Min. temperatura medija [°C]	-20
Material	Stainless steel 1.4404
Navoj	R 1/8
Primerni materiali za cevi	PVDF, PTFE, PA, PU
Standardni navoj	ISO 7-1
Za cevi O.D. [mm]	6
Delovni tlak pulzira [bar]	10
a/f [mm]	13
Max. delovni tlak [bar]	15
L2 [mm]	20.0
L1 [mm]	21.5
Max. delovna temperatura [°C]	150
Max. temperatura medija [°C]	150