



(slika je simbolična)

Vtični T-okovja »Click-klak«, vrtljivi, G 1/2 o.

Kategorija: [Male branch tees with inner hex, swivel type](#)
Šifra: **108689RIE**

Kratek opis

Push-in T-fitting »click-clock«, rotating, G 1/2 o., hose exterior Ø 12, Working pressure -0.99 to 16 bar, nickel-plated brass

The advanced version of our highly successful push-in fittings series manufactured in nickel-plated brass.

Advantages of this new, optimised series:

- Much easier connection and disconnection of the hose, even with repeated mounting
- Can also be used for non-calibrated hoses
- Suitable for vacuum operation

Tehnične Specifikacije

| | |
|-------------------------------|---------------------|
| Min. delovna temperatura [°C] | -20 |
| Min. delovni tlak [bar] | -0.99 |
| Material | Nickel-plated brass |
| Navoj | G 1/2 |
| Priporočena cev | PA, PU |
| Rokav | Hostaform |
| Serijska | click-clock |
| Vpenjalni obroč a/f [mm] | 8 |
| Za cevi O.D. [mm] | 12 |
| Max. delovni tlak [bar] | 16 |
| L2 [mm] | 40.8 |
| L1 [mm] | 73.0 |
| Max. delovna temperatura [°C] | 80 |