

Datum: 10.05.2026



(slika je simbolična)

Vtični T-okovja »Click-klak«, vrtljivi, G 3/8 o.

Kategorija: [Male branch tee, swivel type, parallel male thread](#)
Šifra: **108661RIE**

Kratek opis

Push-in T-fitting »click-clock«, rotating, G 3/8 o., hose exterior Ø 12, Working pressure -0.99 to 16 bar, nickel-plated brass

The advanced version of our highly successful push-in fittings series manufactured in nickel-plated brass.

Advantages of this new, optimised series:

- Much easier connection and disconnection of the hose, even with repeated mounting
- Can also be used for non-calibrated hoses
- Suitable for vacuum operation

Tehnične Specifikacije

| | |
|-------------------------------|---------------------|
| Min. delovna temperatura [°C] | -20 |
| Min. delovni tlak [bar] | -0.99 |
| Material | Nickel-plated brass |
| Navoj | G 3/8 |
| Priporočena cev | PA, PU |
| Rokav | Hostaform |
| Serija | click-clock |
| Vpenjalni obroč | Stainless steel |
| Za cevi O.D. [mm] | 12 |
| Max. delovni tlak [bar] | 16 |
| a/f [mm] | 17 |
| L2 [mm] | 27.1 |
| L1 [mm] | 59.0 |
| Max. delovna temperatura [°C] | 80 |